

```
# In case you want to add a .htpasswd authentication
# you'll have to add the host of the shop as an allowed entity,
# so that calls from the host skip the authentication
# Example:
# Order Deny,Allow
# Deny from All
# AuthType Basic
# AuthName "Access not allowed"
# AuthUserFile path_to_htpasswd_file/.htpasswd
# Require valid-user
# Allow from localhost
# Satisfy Any

<IfModule mod_rewrite.c>
Options +FollowSymLinks
RewriteEngine On
RewriteBase /

RewriteCond %{REQUEST_URI} config\.inc\.php [NC]
RewriteRule ^config\.inc\.php index\.php [R=301,L]

RewriteCond %{QUERY_STRING} ^fnc=(getShopVersion|getShopEdition|getRevision) [NC]
RewriteRule ^(.*)$ $1? [R=301,L]

RewriteCond %{REQUEST_METHOD} ^(TRACE|TRACK)
RewriteRule .* - [F]

RewriteCond %{REQUEST_URI} oxseo\.php$
RewriteCond %{QUERY_STRING} mod_rewrite_module_is=off
RewriteRule oxseo\.php$ oxseo.php?mod_rewrite_module_is=on [L]

RewriteCond %{REQUEST_URI} !^(/admin|/core|/application|/export|/modules|/out|/setup|/tmp|/views)
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule !\.(html|xml|jpg|css|pdf|doc|gif|png|js|html|svg)$ %{REQUEST_URI} [R=301,L]

RewriteCond %{REQUEST_URI} !^(/admin|/core|/application|/export|/modules|/out|/setup|/tmp|/views)
RewriteCond %{REQUEST_FILENAME} !-
```

```
RewriteCond %{REQUEST_FILENAME} !-t
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule (.html|)$ oxseo.php

RewriteCond %{REQUEST_URI} (^|/out/pictures/)
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule (.jpe?g|.gif|.png|.svg)$ getimg.php

</IfModule>

# disabling log file access from outside
<FilesMatch "(EXCEPTION_LOG|.txt|.log$|.tpl$|.pkg|.rev|.ini|.pkg|.info|.pem$)">
order allow,deny
deny from all
</FilesMatch>

Options -Indexes
DirectoryIndex index.php index.html
```