

```

IndexIgnore *
AddType text/cache-manifest .manifest
<IfModule mod_headers.c>
    Header set X-UA-Compatible "IE=Edge,chrome=1"
    # mod_headers can't match by content-type, but we don't want to send this header on *evr
    <FilesMatch "\.(js|css|gif|png|jpe?
gl|pdf|xml|ogal|ogg|m4a|ogv|mp4|m4v|webm|svg|svgz|eot|ttf|otf|woff|ico|webp|appcache|manifest|
>
    Header unset X-UA-Compatible
    </FilesMatch>
</IfModule>

# -----
# Gzip compression
# -----

<IfModule mod_deflate.c>

# Force deflate for mangled headers developer.yahoo.com/blogs/ydn/posts/2010/12/pushing-bey
<IfModule mod_setenvif.c>
    <IfModule mod_headers.c>
        SetEnvIfNoCase ^(\Accept-EncodXng|X-cept-Encoding|X(15)|^(15)|-(15))$ ^((gzip|deflate)\s
HAVE_Accept-Encoding
        RequestHeader append Accept-Encoding "gzip,deflate" env=HAVE_Accept-Encoding
    </IfModule>
</IfModule>

# HTML, TXT, CSS, JavaScript, JSON, XML, HTC:
<IfModule filter_module>
    FilterDeclare COMPRESS
    FilterProvider COMPRESS DEFLATE resp=Content-Type $text/html
    FilterProvider COMPRESS DEFLATE resp=Content-Type $text/css
    FilterProvider COMPRESS DEFLATE resp=Content-Type $text/plain
    FilterProvider COMPRESS DEFLATE resp=Content-Type $text/xml
    FilterProvider COMPRESS DEFLATE resp=Content-Type $text/x-component
    FilterProvider COMPRESS DEFLATE resp=Content-Type $application/javascript
    FilterProvider COMPRESS DEFLATE resp=Content-Type $application/json
    FilterProvider COMPRESS DEFLATE resp=Content-Type $application/xml
    FilterProvider COMPRESS DEFLATE resp=Content-Type $application/xhtml+xml
    FilterProvider COMPRESS DEFLATE resp=Content-Type $application/rss+xml
    FilterProvider COMPRESS DEFLATE resp=Content-Type $application/atom+xml

```

```

FilterProvider COMPRESS DEFLATE resp=Content-Type $application/atom+xml
FilterProvider COMPRESS DEFLATE resp=Content-Type $application/vnd.ms-fontobject
FilterProvider COMPRESS DEFLATE resp=Content-Type $image/svg+xml
FilterProvider COMPRESS DEFLATE resp=Content-Type $application/x-font-ttf
FilterProvider COMPRESS DEFLATE resp=Content-Type $font/opentype
FilterChain COMPRESS
FilterProtocol COMPRESS DEFLATE change=yes;byteranges=no
</IfModule>

<IfModule !mod_filter.c>
# Legacy versions of Apache
AddOutputFilterByType DEFLATE text/html text/plain text/css application/json
AddOutputFilterByType DEFLATE application/javascript
AddOutputFilterByType DEFLATE text/xml application/xml text/x-component
AddOutputFilterByType DEFLATE application/xhtml+xml application/rss+xml application/atom+
AddOutputFilterByType DEFLATE image/svg+xml application/vnd.ms-fontobject application/x-fc
</IfModule>
</IfModule>

# -----
# UTF-8 encoding
# -----

# Use UTF-8 encoding for anything served text/plain or text/html
AddDefaultCharset utf-8

# Force UTF-8 for a number of file formats
AddCharset utf-8 .html .css .js .xml .json .rss .atom

# -----
# Start rewrite engine
# -----

# Turning on the rewrite engine is necessary for the following rules and features.
# FollowSymLinks must be enabled for this to work.

<IfModule mod_rewrite.c>
Options +FollowSymLinks
RewriteEngine On
</IfModule>

# -----
# Add support for the mod_authnz_external, mod_authnz_ldap,
# mod_authnz_otp, mod_authnz_sasl, and mod_authnz_soc
# authentication modules.
# -----

```

```
# Block access to "hidden" directories whose names begin with a period. This  
# includes directories used by version control systems such as Subversion or Git.  
<IfModule mod_rewrite.c>  
    RewriteRule "(^/)\." - [F]  
</IfModule>  
  
<Files channel.html>  
Header add "Expires" "Mon, 28 Jul 2014 23:30:00 GMT"  
Header add "Cache-Control" "max-age=31536000"  
</Files>
```