

ErrorDocument 404 /error/404.html

ErrorDocument 403 /error/403.html

<IfModule mod_rewrite.c>

RewriteEngine On

RewriteBase /

Legacy old URLs

RewriteCond %{REQUEST_FILENAME} !-d

RewriteCond %{REQUEST_FILENAME} !-f

RewriteRule ^(index|home)\.php\$ / [L, R, QSA]

Custom rules for Software

Software version check for widgets

RewriteCond %{REQUEST_FILENAME} !-d

RewriteCond %{REQUEST_FILENAME} !-f

RewriteRule ^software/widgets/versioncheck/([^/]+)\$ /router.php?

controller=software&action=widgets_versioncheck&software_name=\$1 [L, QSA]

Software version check for widgets

RewriteCond %{REQUEST_FILENAME} !-d

RewriteCond %{REQUEST_FILENAME} !-f

RewriteRule ^software/widgets/versioncheck(.*)\$ /router.php?

controller=software&action=widgets_versioncheck [L, QSA]

Software details page

RewriteCond %{REQUEST_FILENAME} !-d

RewriteCond %{REQUEST_FILENAME} !-f

RewriteRule ^software/(macosx|widgets)/([^/]+)\.html\$ /router.php?

controller=software&action=show&software_type=\$1&software_name=\$2&subview=main [L, QSA]

Software default details page

RewriteCond %{REQUEST_FILENAME} !-d

RewriteCond %{REQUEST_FILENAME} !-f

RewriteRule ^software/(macosx|widgets)/([^/]+)/([^/]+)\.html\$ /router.php?

controller=software&action=show&software_type=\$1&software_name=\$2&subview=\$3 [L, QSA]

Software actions

RewriteCond %{REQUEST_FILENAME} !-d

```

RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{REQUEST_FILENAME} !-f
RewriteRule ^software/(download)/([^/]+)/?(.+)?$ /router.php?
controller=software&action=$1&id=$2 [L, QSA]

# Sparkle actions
RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{REQUEST_FILENAME} !-f
RewriteRule ^software/appcast/([^/]+)/?$ /router.php?controller=sparkle&software_name=$1
[L, QSA]

# Sparkle actions
RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{REQUEST_FILENAME} !-f
RewriteRule ^software/(macosx|widgets)/([^/]+)/appcast/?$ /router.php?
controller=sparkle&software_name=$2 [L, QSA]

# Software, old pages
RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{REQUEST_FILENAME} !-f
RewriteRule ^software/(macosx|widgets)/([^\./]+)/?$ /software/$1/$2.html [R, QSA]

RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{REQUEST_FILENAME} !-f
RewriteRule ^software/(macosx|widgets)/([^/]+)/([^\0-9\./]+)/?$ /software/$1/$2/$3.html
[R, QSA]

RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{REQUEST_FILENAME} !-f
RewriteRule ^software/(macosx|widgets)/([^/]+)/download/?(^/)+\.(dmg|zip)$
/software/$1/$2.html [R, QSA]

# Feeds
RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{REQUEST_FILENAME} !-f
RewriteRule ^atom/([^/)+.atom$ /router.php?controller=atom&action=$1 [L, QSA]

RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{REQUEST_FILENAME} !-f
RewriteRule ^feed/([^/)+.rss$ /router.php?controller=feed&action=$1 [L, QSA]

```

```

# KML
RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{REQUEST_FILENAME} !-f
RewriteRule ^kml/([^/]+).kml$ /router.php?controller=kml&action=$1 [L, QSA]

# Errors
RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{REQUEST_FILENAME} !-f
RewriteRule ^error/([^/]+).html$ /router.php?controller=error&action=_$1 [L, QSA]

# Diario, by date
RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{REQUEST_FILENAME} !-f
RewriteRule ^diario/(calendar|date)/([0-9]{4})/?([0-9]{1,2})?/?([0-9]{1,2})?/?$
/router.php?controller=diario&action=$1&year=$2&month=$3&day=$4 [L, QSA]

# Text assets are zipped to save bandwidth
RewriteRule ^assets/(javascript|styles)(/([^/]+)*)/([^/]+\.(?:\.[^.]*)?)$ /router.php?
controller=asset&action=index&dir=$1$2&file=$4&ext=$5 [L, QSA]

# Default rules

# Controller alone
RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{REQUEST_FILENAME} !-f
RewriteRule ^([^/]+\.(html|js(on)?|png|jpe?g|css))$ /router.php?controller=$1 [L, QSA]

# Controller, with action
RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{REQUEST_FILENAME} !-f
RewriteRule ^([^/]+)/([^/]+\.(html|js(on)?|png|jpe?g|css))$ /router.php?
controller=$1&action=$2 [L, QSA]

# Controller, action and id of target
RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{REQUEST_FILENAME} !-f
RewriteRule ^([^/]+)/([^/]+)/([^/]+\.(html|js(on)?|png|jpe?g|css))$ /router.php?controller=$1&action=$2&id=$3 [L, QSA]

# Controller without extension
RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{REQUEST_FILENAME} !-f

```

```
RewriteRule ^([\^/]+)?/$ /$1.html [R,L,QSA]
```

```
# Default controller
```

```
RewriteRule ^$ home.html [L,QSA]
```

```
</IfModule>
```