

```

# BEGIN WordPress
<IfModule mod_rewrite.c>
RewriteEngine On
RewriteBase /eatart.org/
RewriteRule ^index\.php$ - [L]
RewriteRule ^css/(.*) /eatart.org/wp-content/themes/eatart.org/css/$1 [QSA,L]
RewriteRule ^js/(.*) /eatart.org/wp-content/themes/eatart.org/js/$1 [QSA,L]
RewriteRule ^img/(.*) /eatart.org/wp-content/themes/eatart.org/img/$1 [QSA,L]
RewriteRule ^plugins/(.*) /eatart.org/wp-content/plugins/$1 [QSA,L]
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule . /eatart.org/index.php [L]
</IfModule>

# -----
# Better website experience for IE users
# -----

# Force the latest IE version, in various cases when it may fall back to IE7 mode
# github.com/rails/rails/commit/123eb25#commitcomment-118920
# Use ChromeFrame if it's installed for a better experience for the poor IE folk

<IfModule mod_setenvif.c>
  <IfModule mod_headers.c>
    BrowserMatch MSIE ie
    Header set X-UA-Compatible "IE=Edge,chrome=1" env=ie
  </IfModule>
</IfModule>

<IfModule mod_headers.c>
# Because X-UA-Compatible isn't sent to non-IE (to save header bytes),
# We need to inform proxies that content changes based on UA
  Header append Vary User-Agent
# Cache control is set only if mod_headers is enabled, so that's unnecessary to declare
</IfModule>

# -----
# Cross-domain AJAX requests
# -----

# Some cross domain ajax requests disabled

```

```
# serve cross-domain ajax requests, disabled,
# enable-cors.org
# code.google.com/p/html5security/wiki/CrossOriginRequestSecurity

# <IfModule mod_headers.c>@
# </IfModule>

# -----
# Webfont access
# -----

# allow access from all domains for webfonts
# alternatively you could only whitelist
# your subdomains like "sub.domain.com"

<FilesMatch "\.(ttf|otf|eot|woff|font. css)$">
  <IfModule mod_headers.c>@
  </IfModule>
</FilesMatch>

# -----
# Proper MIME type for all files
# -----

# audio
AddType audio/ogg                oga ogg

# video
AddType video/ogg                ogv
AddType video/mp4                mp4
AddType video/webm               webm

# Proper svg serving. Required for svg webfonts on iPad
# twitter.com/FontSquirrel/status/14855840545
AddType image/svg+xml           svg svgz
AddEncoding gzip                svgz

# webfonts
AddType application/vnd.ms-fontobject eot
AddType font/truetype             ttf
AddType font/opentype             otf
AddType font/woff                 woff
AddType font/woff2                 woff2
```

```

AddType application/x-font-woff          woff

# assorted types
AddType image/x-icon                    ico
AddType image/webp                      webp
AddType text/cache-manifest              appcache manifest
AddType text/x-component                 htc
AddType application/x-chrome-extension  crx
AddType application/x-xpinstall          xpi
AddType application/octet-stream         safariextz

# -----
# gzip compression
# -----

<IfModule mod_deflate.c>

# force deflate for mangled headers developer.yahoo.com/blogs/ymh/posts/2010/12/pushing-beyond-gzipping/
<IfModule mod_setenvif.c>
  <IfModule mod_headers.c>
    SetEnvIfNoCase ^(\Accept-EncodXngl X-cept-Encodingl X(15)l ~(15)l -(15))$
    ^((gzip| deflate)\s, ?\s(gzip| deflate)?l X(4,13)l ~(4,13)l -(4,13))$ HAVE_Accept-Encoding
    RequestHeader append Accept-Encoding "gzip, deflate" env=HAVE_Accept-Encoding
  </IfModule>
</IfModule>

# html, txt, css, js, json, xml, htc:
<IfModule filter_module>
  FilterDeclare      COMPRESS
  FilterProvider     COMPRESS DEFLATE resp=Content-Type
  /text/(html| css| javascript| plain| x(ml| -component))/
  FilterProvider     COMPRESS DEFLATE resp=Content-Type /application/(javascript| json| xml| x-
  javascript)/
  FilterChain        COMPRESS
  FilterProtocol     COMPRESS  change=yes;byteranges=no
</IfModule>

<IfModule !mod_filter.c>
  # Legacy versions of Apache
  AddOutputFilterByType DEFLATE text/html text/plain text/css application/json
  AddOutputFilterByType DEFLATE text/javascript application/javascript application/x-

```

javascript

```
AddOutputFilterByType DEFLATE text/xml application/xml text/x-component
</IfModule>
```

webfonts and svg:

```
<FilesMatch "\.(ttf|otf|eot|svg)$" >
    SetOutputFilter DEFLATE
</FilesMatch>
</IfModule>
```

```
# -----
# Stop screen flicker in IE on CSS rollovers
# -----
```

*# The following directives stop screen flicker in IE on CSS rollovers - in
combination with the "ExpiresByType" rules for images (see above). If
needed, un-comment the following rules.*

```
# BrowserMatch "MSIE" brokenvary=1
# BrowserMatch "Mozilla/4.[0-9]{2}" brokenvary=1
# BrowserMatch "Opera" !brokenvary
# SetEnvIf brokenvary 1 force-no-vary
```

```
# -----
# Prevent SSL cert warnings
# -----
```

*# Rewrite secure requests properly to prevent SSL cert warnings, e.g. prevent
https://www.domain.com when your cert only allows https://secure.domain.com
Uncomment the following lines to use this feature.*

```
# <IfModule mod_rewrite.c>
#   RewriteCond %{SERVER_PORT} !^443
#   RewriteRule (.*) https://example-domain-please-change-me.com/$1 [R=301,L]
# </IfModule>
```

```
# -----
# Prevent 404 errors for non-existing redirected folders
# -----
```

without -MultiViews, Apache will give a 404 for a rewrite if a folder of the same name

does not exist

e.g. /blog/hello : webmasterworld.com/apache/3808792.htm

Options -MultiViews

```
# -----  
# UTF-8 encoding  
# -----
```

use utf-8 encoding for anything served text/plain or text/html

AddDefaultCharset utf-8

force utf-8 for a number of file formats

AddCharset utf-8 .html .css .js .xml .json .rss

```
# -----  
# A little more security  
# -----
```

Do we want to advertise the exact version number of Apache we're running?

Probably not.

This can only be enabled if used in httpd.conf - It will not work in .htaccess

ServerTokens Prod

*# "-Indexes" will have Apache block users from browsing folders without a default document
Usually you should leave this activated, because you shouldn't allow everybody to surf
through*

*# every folder on your server (which includes rather private places like CMS system
folders).*

Options -Indexes

*# Block access to "hidden" directories whose names begin with a period. This
includes directories used by version control systems such as Subversion or Git.*

```
<IfModule mod_rewrite.c>
```

```
    RewriteRule "(^/)\." - [F]
```

```
</IfModule>
```

*# If your server is not already configured as such, the following directive
should be uncommented in order to set PHP's register_globals option to OFF.*

*# This closes a major security hole that is abused by most XSS (cross-site
scripting) attacks. For more information: http://php.net/register_globals*

```
#
# IF REGISTER_GLOBALS DIRECTIVE CAUSES 500 INTERNAL SERVER ERRORS :
#
# Your server does not allow PHP directives to be set via .htaccess. In that
# case you must make this change in your php.ini file instead. If you are
# using a commercial web host, contact the administrators for assistance in
# doing this. Not all servers allow local php.ini files, and they should
# include all PHP configurations (not just this one), or you will effectively
# reset everything to PHP defaults. Consult www.php.net for more detailed
# information about setting PHP directives.

# php_flag register_globals Off

# Increase cookie security
<IfModule php5_module>
    php_value session.cookie_httponly true
</IfModule>
# END WordPress
```