

```

#
#

# Protect files and directories from prying eyes.
<FilesMatch "\.
(engine|incl|info|install|make|module|profile|test|po|sh|. *sql|them|tpl(\. php)?
|xml|)$|^(\. *|Entries.*|Repository|Root|Tag|Template)$">
    Order allow,deny
</FilesMatch>

# Don't show directory listings for URLs which map to a directory.
Options -Indexes

# Follow symbolic links in this directory.
Options +FollowSymLinks

# Multiviews creates problems with aliased URLs and is not needed for Drupal.
Options -Multiviews

# Make Drupal handle any 404 errors.
ErrorDocument 404 /index.php

# Force simple error message for requests for non-existent favicon.ico.
<Files favicon.ico>
    # There is no end quote below, for compatibility with Apache 1.3.
    ErrorDocument 404 "The requested file favicon.ico was not found.
</Files>

# Set the default handler.
DirectoryIndex index.php index.html index.htm

# Override PHP settings that cannot be changed at runtime. See
# sites/default/default.settings.php and drupal_initialize_variables() in
# includes/bootstrap.inc for settings that can be changed at runtime.

# PHP 5, Apache 1 and 2.
<IfModule mod_php5.c>
    php_flag magic_quotes_gpc          off
    php_flag magic_quotes_sybase      off
    php_flag register_globals         off
    php_flag session.auto_start      off

```

```
php_flag session.auto_start      off
php_value mbstring.http_input    pass
php_value mbstring.http_output   pass
php_flag mbstring.encoding_translation off
</IfModule>
```

*# Requires mod\_expires to be enabled.*

```
<IfModule mod_expires.c>
```

*# Enable expirations.*

```
ExpiresActive On
```

*# Cache all files for 2 weeks after access (A).*

```
ExpiresDefault A1209600
```

```
<FilesMatch \.php$>
```

*# Do not allow PHP scripts to be cached unless they explicitly send cache  
# headers themselves. Otherwise all scripts would have to overwrite the  
# headers set by mod\_expires if they want another caching behavior. This may  
# fail if an error occurs early in the bootstrap process, and it may cause  
# problems if a non-Drupal PHP file is installed in a subdirectory.*

```
ExpiresActive Off
```

```
</FilesMatch>
```

```
</IfModule>
```

*# Various rewrite rules.*

```
<IfModule mod_rewrite.c>
```

```
RewriteEngine On
```

```
RewriteBase /
```

*#Removes access to the system folder by users.  
#Additionally this will allow you to create a System.php controller,  
#previously this would not have been possible.*

*#'system' can be replaced if you have renamed your system folder.*

```
RewriteCond %{REQUEST_URI} ^system.*
```

```
RewriteRule ^(.*)$ /index.php?/$1 [L]
```

*#When your application folder isn't in the system folder*

*#This snippet prevents user access to the application folder*

*#Submitted by: Fabdro1*

*#Rename 'application' to your applications folder name.*

```
RewriteCond %{REQUEST_URI} ^application.*
```

```
RewriteRule ^(.*)$ /index.php?/$1 [L]
```

```
RewriteRule ^(.*)$ /index.php?/$1 [L]
```

```
#Checks to see if the user is attempting to access a valid file,  
#such as an image or css document, if this isn't true it sends the  
#request to index.php
```

```
RewriteCond %(REQUEST_FILENAME) !-f
```

```
RewriteCond %(REQUEST_FILENAME) !-d
```

```
RewriteRule ^(.*)$ index.php?/$1 [L]
```

```
</IfModule>
```

```
<IfModule !mod_rewrite.c>
```

```
# If we don't have mod_rewrite installed, all 404's  
# can be sent to index.php, and everything works as normal.  
# Submitted by: ElliotHaughin
```

```
ErrorDocument 404 /index.php
```

```
</IfModule>
```