

```

AddDefaultCharset utf-8
<IfModule mod_mime.c>
    AddType application/json          json map topjson
    AddType application/xml           rdf xml
    AddType application/javascript    js
    AddType audio/mp4                 f4a f4b m4a
    AddType audio/ogg                 oga ogg opus
    AddType image/bmp                 bmp
    AddType image/svg+xml             svg svgz
    AddType image/webp                webp
    AddType video/mp4                 f4v f4p m4v mp4
    AddType video/ogg                 ogv
    AddType video/webm                webm
    AddType video/x-flv               flv
    AddType image/x-icon              cur ico
    AddType application/font-woff     woff
    AddType application/font-woff2    woff2
    AddType application/vnd.ms-fontobject eot
    AddType application/x-font-ttf    ttc ttf
    AddType font/opentype             otf
    AddType text/x-component          htc
    AddCharset utf-8 .css .js .json .xml
</IfModule>
#
<IfModule mod_deflate.c>
    <IfModule mod_setenvif.c>
        <IfModule mod_headers.c>
            SetEnvIfNoCase ^(\Accept-EncodXngl X-cept-Encodingl X(15)|^(15)|-(15))$
            ^((gzip|deflate)\s*, ?\s*)+ [X"-]{4,13}$ HAVE_Accept-Encoding
            RequestHeader append Accept-Encoding "gzip, deflate" env=HAVE_Accept-Encoding
        </IfModule>
    </IfModule>
<IfModule mod_filter.c>
    SetEnv HTTP_MOD_DEFLATE on
    AddOutputFilterByType DEFLATE "application/javascript" \
        "application/json" \
        "application/vnd.ms-fontobject" \
        "application/x-font-ttf" \
        "application/x-javascript" \
        "application/xhtml+xml" \
        "text/css" \

```

```

        application/xml \
        "font/eot" \
        "font/opentype" \
        "image/bmp" \
        "image/svg+xml" \
        "image/vnd.microsoft.icon" \
        "image/x-icon" \
        "text/cache-manifest" \
        "text/css" \
        "text/html" \
        "text/javascript" \
        "text/plain" \
        "text/x-component" \
        "text/xml"

</IfModule>
<IfModule mod_mime.c>
    AddEncoding gzip          svgz
</IfModule>
</IfModule>
<IfModule mod_headers.c>
    Header unset ETag
</IfModule>
FileETag None
<IfModule mod_expires.c>
    ExpiresActive on
    ExpiresDefault            "access plus 1 month"
</IfModule>
# BEGIN OJii Framework
<IfModule mod_autoindex.c>
    Options -Indexes
</IfModule>
ErrorDocument 403 /error.php?err=403
ErrorDocument 404 /error.php?err=404

<IfModule mod_rewrite.c>
    SetEnv HTTP_MOD_REWRITE on
    RewriteEngine On
    Options +FollowSymLinks
    RewriteBase /
#
#
#

```

```
RewriteRule ^error\.php$ - [QSA,L]
RewriteRule ^template\.php$ - [QSA,L]
RewriteRule ^offline\.php$ - [QSA,L]
RewriteRule ^php/(. *.php)$ / [L,R=404]
#
RewriteCond %{REQUEST_FILENAME} !-f
RewriteRule ^(. *)\_(\[\0-9-\]\+)\. (js|css|png|jpe?g|gif|svg)$ $1.$3?m=$2 [QSA,L]
RewriteRule ^(. *)\. (js|css|png|jpg|gif|svg)$ - [QSA,L]
#
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule . /template.php [QSA]
# remove trailing /
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{REQUEST_URI} (.+)/$
RewriteRule ^ %1 [L,R=301]

</IfModule>
# END O11i Framework
```