```
# Turn off MultiViews
Options -MultiViews
# Directive to ensure *.rdf files served as appropriate content type,
# if not present in main apache config
AddTupe application/rdf+xml .rdf
# This .htaccess file is based on https://www.w3.org/TR/swbp-vocab-pub/#recipe4
# It is configured to use HTTP 303 (See other) and content negotiation so that:
# Requested URI: http://whatever.org/experimental/id/bla
# If 'Accept' header indicates html, then serve
http://whatever.org/experimental/doc/bla.html.
# If 'Accept' header indicates rdf, then serve
http://whatever.org/experimental/doc/bla.rdf.
# Rewrite engine setup
RewriteEngine On
RewriteBase /experimental
# Rewrite rule to serve HTML content from the vocabulary URI if requested
RewriteCond %(HTTP_ACCEPT) !application/rdf\+xml.*(text/html/application/xhtml\+xml)
RewriteCond %(HTTP_ACCEPT) text/html [OR]
RewriteCond %(HTTP_ACCEPT) application/xhtml\+xml [OR]
RewriteCond %(HTTP USER AGENT) ^Mozilla/.*
RewriteRule ^id/(.+)$ doc/$1.html [R=303]
# Rewrite rule to serve directed HTML content from class/prop URIs
#RewriteCond %CHTTP_ACCEPT>!application/rdf\+xml.*(text/html/application/xhtml\+xml)
#RewriteCond %CHTTP_ACCEPT> text/html [OR]
#RewriteCond %(HTTP_ACCEPT) application/xhtml\+xml [OR]
#RewriteCond %(HTTP_USER_AGENT) ^Mozilla/.*
#RewriteRule ^example4/(.+) example4-content/2005-10-31.html#$1 [R=303,NE]
# Rewrite rule to serve RDF/XML content if requested
RewriteCond %(HTTP_ACCEPT) application/rdf\+xml
RewriteRule ^id/(.+) doc/$1.rdf [R=303]
# Choose the default response
# minuffi and it limb merium lilitii bu difini
```

## RewriteRule ^id/(.+) doc/\$1.rdf [R=303]

- # Rewrite rules to serve HTML content by default (disabled)
- # (To enable this option, uncomment the rewrite rules below,
- # and comment out the rewrite rule directly above)
- # RewriteRule ^id/(,+)\$ doc/\$1.html [R=303]