

```

# Apache Server Configs v2.11.0 | MIT License
# https://github.com/h5bp/server-configs-apache
# (!) Using `.htaccess` files slows down Apache, therefore, if you have
# access to the main server configuration file (which is usually called
# `httpd.conf`), you should add this logic there.
#
# https://httpd.apache.org/docs/current/howto/htaccess.html.
# #####
# # CROSS-ORIGIN #
# #####
# -----
# | Cross-origin requests |
# -----
# Allow cross-origin requests.
#
# https://developer.mozilla.org/en-US/docs/Web/HTTP/Access_control_CORS
# http://enable-cors.org/
# http://www.w3.org/TR/cors/
# <IfModule mod_headers.c>
# Header set Access-Control-Allow-Origin "*"
# </IfModule>
# -----
# | Cross-origin images |
# -----
# Send the CORS header for images when browsers request it.
#
# https://developer.mozilla.org/en-US/docs/Web/HTML/CORS_enabled_image
# https://blog.chromium.org/2011/07/using-cross-domain-images-in-webgl-and.html
<IfModule mod_setenvif.c>
<IfModule mod_headers.c>
<FilesMatch "\.(bmp|curl gif|icol jpe?g|png|svgz?|webp)$">
SetEnvIf Origin ":" IS_CORS
Header set Access-Control-Allow-Origin "*" env=IS_CORS
</FilesMatch>
</IfModule>
</IfModule>
# -----
# | Cross-origin web fonts |
# -----
# Allow cross-origin access to web fonts.
<IfModule mod_headers.c>

```

```
<!IfModule mod_headers.c>
<FilesMatch "\.(eot|otfltt[cf]lwoff2?)$">
Header set Access-Control-Allow-Origin "*"
</FilesMatch>
</IfModule>
# -----
# | Cross-origin resource timing |
# -----
# Allow cross-origin access to the timing information for all resources.
#
# If a resource isn't served with a `Timing-Allow-Origin` header that
# would allow its timing information to be shared with the document,
# some of the attributes of the `PerformanceResourceTiming` object will
# be set to zero.
#
# http://www.w3.org/TR/resource-timing/
# http://www.stevesouders.com/blog/2014/08/21/resource-timing-practical-tips/
# <IfModule mod_headers.c>
# Header set Timing-Allow-Origin: "*"
# </IfModule>
# #####
# # ERRORS #
# #####
# -----
# | Custom error messages/pages |
# -----
# Customize what Apache returns to the client in case of an error.
# https://httpd.apache.org/docs/current/mod/core.html#errordocument
# ErrorDocument 404 /404.html
# -----
# | Error prevention |
# -----
# Disable the pattern matching based on filenames.
#
# This setting prevents Apache from returning a 404 error as the result
# of a rewrite when the directory with the same name does not exist.
#
# https://httpd.apache.org/docs/current/content-negotiation.html#multiviews
Options -MultiViews
# #####
# # INTERNET EXPLORER #
# .....
```

```

# #####
# -----
# | Document modes |
# -----
# Force Internet Explorer 8/9/10 to render pages in the highest mode
# available in the various cases when it may not.
#
# https://hsivonen.fi/doctype/#ie8
#
# (!) Starting with Internet Explorer 11, document modes are deprecated.
# If your business still relies on older web apps and services that were
# designed for older versions of Internet Explorer, you might want to
# consider enabling `Enterprise Mode` throughout your company.
#
# http://msdn.microsoft.com/en-us/library/ie/bg182625.aspx#docmode
# http://blogs.msdn.com/b/ie/archive/2014/04/02/stay-up-to-date-with-enterprise-mode-for-
internet-explorer-11.aspx
<IfModule mod_headers.c>
Header set X-UA-Compatible "IE=edge"
# `mod_headers` cannot match based on the content-type, however,
# the `X-UA-Compatible` response header should be send only for
# HTML documents and not for the other resources.
<FilesMatch "\.
(appache|atom|bbaw|bml|crl|css|curl|eot|f4[abpv]|flv|geojson|gif|htcl|icol|jpe?
|j|j|json|ld)?
|m4[av]|manifest|map|mp4|oex|og[agv]|opus|otf|pdf|png|rdf|rssl|safariextz|svgz?
|swf|topojson|tt[cf]|txt|vcard|vcf|vtl|webapp|web[mp]|woff2?|xlcl|xml|xpi)$">
Header unset X-UA-Compatible
</FilesMatch>
</IfModule>
# -----
# | Iframes cookies |
# -----
# Allow cookies to be set from iframes in Internet Explorer.
#
# http://msdn.microsoft.com/en-us/library/ms537343.aspx
# http://www.w3.org/TR/2000/CR-P3P-20001215/
# <IfModule mod_headers.c>
# Header set P3P "policyref=\"/w3c/p3p.xml\", CP=\"IDC DSP COR ADM DEVI TAIi PSA PSD IVAi
IVDi CONi HIS OUR IND CNT\""
# </IfModule>

```

```
# #####
# # MEDIA TYPES AND CHARACTER ENCODINGS #
# #####
# -----
# | Media types |
# -----
# Serve resources with the proper media types (f. k. a. MIME types).
#
# https://www.iana.org/assignments/media-types/media-types.xhtml
# https://httpd.apache.org/docs/current/mod/mod_mime.html#addtype
<IfModule mod_mime.c>
# Data interchange
AddType application/json json map topojson
AddType application/ld+json jsonld
AddType application/vnd.geo+json geojson
AddType application/xml atom rdf rss xml
# JavaScript
# Normalize to standard type.
# https://tools.ietf.org/html/rfc4329#section-7.2
AddType application/javascript js
# Manifest files
# If you are providing a web application manifest file (see
# the specification: https://w3c.github.io/manifest/), it is
# recommended that you serve it with the `application/manifest+json`
# media type.
#
# Because the web application manifest file doesn't have its
# own unique file extension, you can set its media type either
# by matching:
#
# 1) the exact location of the file (this can be done using a
# directive such as ``, but it will NOT work in
# the `.htaccess` file, so you will have to do it in the main
# server configuration file or inside of a ``
# container)
#
# e. g.:
#
# <Location "/.well-known/manifest.json">
# AddType application/manifest+json json
# </Location>
```

```
#
# 2) the filename (this can be problematic as you will need to
# ensure that you don't have any other file with the same name
# as the one you gave to your web application manifest file)
#
# e. g. :
#
# <Files "manifest.json">
# AddType application/manifest+json json
# </Files>
AddType application/x-web-app-manifest+json webapp
AddType text/cache-manifest appcache manifest
# Media files
AddType audio/mp4 f4a f4b m4a
AddType audio/ogg oga ogg opus
AddType image/bmp bmp
AddType image/svg+xml svg svgz
AddType image/webp webp
AddType video/mp4 f4v f4p m4v mp4
AddType video/ogg ogv
AddType video/webm webm
AddType video/x-flv flv
# Serving `.ico` image files with a different media type
# prevents Internet Explorer from displaying them as images:
# https://github.com/h5bp/html5-
boilerplate/commit/37b5fec090d00f38de64b591bcddcb205aadf8ee
AddType image/x-icon cur ico
# Web fonts
AddType application/font-woff woff
AddType application/font-woff2 woff2
AddType application/vnd.ms-fontobject eot
# Browsers usually ignore the font media types and simply sniff
# the bytes to figure out the font type.
# https://mimesniff.spec.whatwg.org/#matching-a-font-type-pattern
#
# However, Blink and WebKit based browsers will show a warning
# in the console if the following font types are served with any
# other media types.
AddType application/x-font-ttf ttc ttf
AddType font/opentype otf
# Other
```

```
AddType application/octet-stream safariextz
AddType application/x-bb-appworld bbaw
AddType application/x-chrome-extension crx
AddType application/x-opera-extension oex
AddType application/x-xpinstall xpi
AddType text/vcard vcard vcf
AddType text/vnd.rim.location.xloc xloc
AddType text/vtt vtt
AddType text/x-component htc
</IfModule>
# -----
# | Character encodings |
# -----
# Serve all resources labeled as `text/html` or `text/plain`
# with the media type `charset` parameter set to `UTF-8`.
#
# https://httpd.apache.org/docs/current/mod/core.html#adddefaultcharset
AddDefaultCharset utf-8
# -----
# Serve the following file types with the media type `charset`
# parameter set to `UTF-8`.
#
# https://httpd.apache.org/docs/current/mod/mod_mime.html#addcharset
<IfModule mod_mime.c>
AddCharset utf-8 .atom \
.bbaw \
.css \
.geojson \
.js \
.json \
.jsonld \
.rdf \
.rss \
.topojson \
.vtt \
.webapp \
.xloc \
.xml
</IfModule>
# #####
# # REWRITES #
```

```
# #####
# -----
# | Rewrite engine |
# -----
# (1) Turn on the rewrite engine (this is necessary in order for
# the `RewriteRule` directives to work).
#
# https://httpd.apache.org/docs/current/mod/mod\_rewrite.html#RewriteEngine
#
# (2) Enable the `FollowSymLinks` option if it isn't already.
#
# https://httpd.apache.org/docs/current/mod/core.html#options
#
# (3) If your web host doesn't allow the `FollowSymLinks` option,
# you need to comment it out or remove it, and then uncomment
# the `Options +SymLinksIfOwnerMatch` line (4), but be aware
# of the performance impact.
#
# https://httpd.apache.org/docs/current/misc/perf-tuning.html#symlinks
#
# (4) Some cloud hosting services will require you set `RewriteBase`.
#
# http://www.rackspace.com/knowledge\_center/frequently-asked-question/why-is-modrewrite-not-working-on-my-site
# https://httpd.apache.org/docs/current/mod/mod\_rewrite.html#rewritebase
#
# (5) Depending on how your server is set up, you may also need to
# use the `RewriteOptions` directive to enable some options for
# the rewrite engine.
#
# https://httpd.apache.org/docs/current/mod/mod\_rewrite.html#rewriteoptions
#
# (6) Set %(ENV:PROTO) variable, to allow rewrites to redirect with the
# appropriate schema automatically (http or https).
<IfModule mod_rewrite.c>
# (1)
RewriteEngine On
# (2)
Options +FollowSymLinks
# (3)
Options +SymLinksIfOwnerMatch
```

```
# (4)
# RewriteBase /
# (5)
# RewriteOptions <options>
# (6)
RewriteCond %{HTTPS} =on
RewriteRule ^ - [env=proto:https]
RewriteCond %{HTTPS} !=on
RewriteRule ^ - [env=proto:http]
</IfModule>

# -----
# | Forcing `https://` |
# -----
# Redirect from the `http://` to the `https://` version of the URL.
# https://wiki.apache.org/httpd/RewriteHTTPToHTTPS
# <IfModule mod_rewrite.c>
# RewriteEngine On
# RewriteCond %{HTTPS} !=on
# RewriteRule ^(.*)$ https://%{HTTP_HOST}/$1 [R=301,L]
# </IfModule>

# -----
# | Suppressing / Forcing the `www.` at the beginning of URLs |
# -----
# The same content should never be available under two different
# URLs, especially not with and without `www.` at the beginning.
# This can cause SEO problems (duplicate content), and therefore,
# you should choose one of the alternatives and redirect the other
# one.
#
# By default `Option 1` (no `www.`) is activated.
# http://no-www.org/faq.php?q=class_b
#
# If you would prefer to use `Option 2`, just comment out all the
# lines from `Option 1` and uncomment the ones from `Option 2`.
#
# (!) NEVER USE BOTH RULES AT THE SAME TIME!
# -----
# Option 1: rewrite www.example.com + example.com
<IfModule mod_rewrite.c>
RewriteEngine On
RewriteCond %{HTTPS} !=on
```



```
-----
RewriteCond %{HTTP_HOST} ^www\.(.+$) [NC]
RewriteRule ^ %{ENV:PROTO}://%1%{REQUEST_URI} [R=301,L]
</IfModule>
# -----
# Option 2: rewrite example.com + www.example.com
#
# Be aware that the following might not be a good idea if you use "real"
# subdomains for certain parts of your website.
# <IfModule mod_rewrite.c>
# RewriteEngine On
# RewriteCond %{HTTPS} !=on
# RewriteCond %{HTTP_HOST} !^www\. [NC]
# RewriteCond %{SERVER_ADDR} !=127.0.0.1
# RewriteCond %{SERVER_ADDR} !=::1
# RewriteRule ^ %{ENV:PROTO}://www.%{HTTP_HOST}%{REQUEST_URI} [R=301,L]
# </IfModule>
# #####
# # SECURITY #
# #####
# -----
# | Clickjacking |
# -----
# Protect website against clickjacking.
#
# The example below sends the `X-Frame-Options` response header with
# the value `DENY`, informing browsers not to display the content of
# the web page in any frame.
#
# This might not be the best setting for everyone. You should read
# about the other two possible values the `X-Frame-Options` header
# field can have: `SAMEORIGIN` and `ALLOW-FROM`.
# https://tools.ietf.org/html/rfc7034#section-2.1.
#
# Keep in mind that while you could send the `X-Frame-Options` header
# for all of your website's pages, this has the potential downside that
# it forbids even non-malicious framing of your content (e.g.: when
# users visit your website using a Google Image Search results page).
#
# Nonetheless, you should ensure that you send the `X-Frame-Options`
# header for all pages that allow a user to make a state changing
# operation (e.g. pages that contain one-click purchase links, checkout
```

```
# operations (e.g., pages that contain one-click purchase links, checkout
# or bank-transfer confirmation pages, pages that make permanent
# configuration changes, etc.).
#
# Sending the `X-Frame-Options` header can also protect your website
# against more than just clickjacking attacks:
# https://cure53.de/xfo-clickjacking.pdf.
#
# https://tools.ietf.org/html/rfc7034
# http://blogs.msdn.com/b/ieinternals/archive/2010/03/30/combating-clickjacking-with-x-
frame-options.aspx
# https://www.owasp.org/index.php/Clickjacking
# <IfModule mod_headers.c>
# Header set X-Frame-Options "DENY"
# # `mod_headers` cannot match based on the content-type, however,
# # the `X-Frame-Options` response header should be send only for
# # HTML documents and not for the other resources.
# <FilesMatch "\.
(appcache|atom|bbaw|bmp|crx|css|curl|eot|f4[abpw]|flv|geo.json|gif|html|ico|jpe?
|j|j|json(1d)?
|m4[av]|manifest|map|mp4|oex|og[agv]|opus|otf|pdf|png|rdf|rss|safariextz|svgz?
|swf|topo.json|tt[cf]|txt|vcard|vcf|vtt|webapp|web[mp]|woff2?|x|oc|x|xp|)$">
# Header unset X-Frame-Options
# </FilesMatch>
# </IfModule>
# -----
# | Content Security Policy (CSP) |
# -----
# Mitigate the risk of cross-site scripting and other content-injection
# attacks.
#
# This can be done by setting a `Content Security Policy` which
# whitelists trusted sources of content for your website.
#
# The example header below allows ONLY scripts that are loaded from the
# current website's origin (no inline scripts, no CDN, etc). That almost
# certainly won't work as-is for your website!
#
# For more details on how to craft a reasonable policy for your website,
# read: http://www.html5rocks.com/en/tutorials/security/content-security-policy/
# (or the specification: http://www.w3.org/TR/CSP11/). Also, to make
# these rules work you may need to either CSP header separated with an
```

```
# things easier, you can use an online CSP header generator such as:
# http://cspisawesome.com/.
# <IfModule mod_headers.c>
# Header set Content-Security-Policy "script-src 'self'; object-src 'self'"
# # `mod_headers` cannot match based on the content-type, however,
# # the `Content-Security-Policy` response header should be send
# # only for HTML documents and not for the other resources.
# <FilesMatch "\.
(appcache|atom|bbaw|bmap|crl|css|curl|eot|f4[abpw]|flv|geojson|gif|htcl|icol|jpe?
gl|jsl|json(1d)?
|m4[av]|manifest|map|mp4|oex|og[agv]|opus|otf|pdf|png|rdf|rssl|safariextz|svgz?
|swf|topojson|tt[cf]|txt|vcard|vcf|vtt|webapp|web[mp]|woff2?|xlocl|xml|xpi)$">
# Header unset Content-Security-Policy
# </FilesMatch>
# </IfModule>
# -----
# | File access |
# -----
# Block access to directories without a default document.
#
# You should leave the following uncommented, as you shouldn't allow
# anyone to surf through every directory on your server (which may
# includes rather private places such as the CMS's directories).
<IfModule mod_autoindex.c>
Options -Indexes
</IfModule>
# -----
# Block access to all hidden files and directories with the exception of
# the visible content from within the `/.well-known/` hidden directory.
#
# These types of files usually contain user preferences or the preserved
# state of an utility, and can include rather private places like, for
# example, the `.git` or `.svn` directories.
#
# The `/.well-known/` directory represents the standard (RFC 5785) path
# prefix for "well-known locations" (e.g.: `/.well-known/manifest.json`,
# `/.well-known/keybase.txt`), and therefore, access to its visible
# content should not be blocked.
#
# https://www.mnot.net/blog/2010/04/07/well-known
# https://tools.ietf.org/html/rfc5785
```

```

<IfModule mod_rewrite.c>
RewriteEngine On
RewriteCond %{REQUEST_URI} "!(^/)\.well-known/([^. /]+. /?)+$" [NC]
RewriteCond %{SCRIPT_FILENAME} -d [OR]
RewriteCond %{SCRIPT_FILENAME} -f
RewriteRule "(^/)\." - [F]
</IfModule>

# -----
# Block access to files that can expose sensitive information.
#
# By default, block access to backup and source files that may be
# left by some text editors and can pose a security risk when anyone
# has access to them.
#
# http://feross.org/cmsexploit/
#
# (!) Update the `<FilesMatch>` regular expression from below to
# include any files that might end up on your production server and
# can expose sensitive information about your website. These files may
# include: configuration files, files that contain metadata about the
# project (e.g.: project dependencies), build scripts, etc..
<FilesMatch "(^#.##\.(bak|conf|dist|fla|in[ci]|log|psd|sh|sql|sw[op])|")$" >
# Apache < 2.3
<IfModule !mod_authz_core.c>
Order allow,deny
Deny from all
Satisfy All
</IfModule>
# Apache ≥ 2.3
<IfModule mod_authz_core.c>
Require all denied
</IfModule>
</FilesMatch>

# -----
# | HTTP Strict Transport Security (HSTS) |
# -----
# Force client-side SSL redirection.
#
# If a user types `example.com` in their browser, even if the server
# redirects them to the secure version of the website, that still leaves
# a window of opportunity (the initial HTTP connection) for an attacker

```

```
# to downgrade or redirect the request.
#
# The following header ensures that browser will ONLY connect to your
# server via HTTPS, regardless of what the users type in the browser's
# address bar.
#
# (!) Remove the `includeSubDomains` optional directive if the website's
# subdomains are not using HTTPS.
#
# http://www.html5rocks.com/en/tutorials/security/transport-layer-security/
# https://tools.ietf.org/html/draft-ietf-websec-strict-transport-sec-14#section-6.1
# http://blogs.msdn.com/b/ieinternals/archive/2014/08/18/hsts-strict-transport-security-attacks-mitigations-deployment-https.aspx
# <IfModule mod_headers.c>
# Header set Strict-Transport-Security "max-age=16070400; includeSubDomains"
# </IfModule>
# -----
# | Reducing MIME type security risks |
# -----
# Prevent some browsers from MIME-sniffing the response.
#
# This reduces exposure to drive-by download attacks and cross-origin
# data leaks, and should be left uncommented, especially if the server
# is serving user-uploaded content or content that could potentially be
# treated as executable by the browser.
#
# http://www.slideshare.net/hasegawayosuke/owasp-hasegawa
# http://blogs.msdn.com/b/ie/archive/2008/07/02/ie8-security-part-v-comprehensive-protection.aspx
# http://msdn.microsoft.com/en-us/library/ie/gg622941.aspx
# https://mimesniff.spec.whatwg.org/
<IfModule mod_headers.c>
Header set X-Content-Type-Options "nosniff"
</IfModule>
# -----
# | Reflected Cross-Site Scripting (XSS) attacks |
# -----
# (1) Try to re-enable the cross-site scripting (XSS) filter built
# into most web browsers.
#
# The filter is usually enabled by default, but in some cases it
```

```
# may be disabled by the user. However, in Internet Explorer for
# example, it can be re-enabled just by sending the
# `X-XSS-Protection` header with the value of `1`.
#
# (2) Prevent web browsers from rendering the web page if a potential
# reflected (a.k. a non-persistent) XSS attack is detected by the
# filter.
#
# By default, if the filter is enabled and browsers detect a
# reflected XSS attack, they will attempt to block the attack
# by making the smallest possible modifications to the returned
# web page.
#
# Unfortunately, in some browsers (e.g.: Internet Explorer),
# this default behavior may allow the XSS filter to be exploited,
# thereby, it's better to inform browsers to prevent the rendering
# of the page altogether, instead of attempting to modify it.
#
# http://hackademix.net/2009/11/21/ies-xss-filter-creates-xss-vulnerabilities
#
# (!) Do not rely on the XSS filter to prevent XSS attacks! Ensure that
# you are taking all possible measures to prevent XSS attacks, the
# most obvious being: validating and sanitizing your website's inputs.
#
# http://blogs.msdn.com/b/ie/archive/2008/07/02/ie8-security-part-iv-the-xss-filter.aspx
# http://blogs.msdn.com/b/ieinternals/archive/2011/01/31/controlling-the-internet-explorer-xss-filter-with-the-x-xss-protection-http-header.aspx
# https://www.owasp.org/index.php/Cross-site\_Scripting\_%28XSS%29
# <IfModule mod_headers.c>
# # (1) (2)
# Header set X-XSS-Protection "1; mode=block"
# # `mod_headers` cannot match based on the content-type, however,
# # the `X-XSS-Protection` response header should be send only for
# # HTML documents and not for the other resources.
# <FilesMatch "\.
(appache|atom|bbaw|bml|crl|css|curl|eot|f4[abpv]|flv|geo.json|gif|htcl|icol|jpe?
gl|jsl|json(1d)?
|m4[av]|manifest|map|mp4|oex|og[agv]|opus|otf|pdf|png|rdf|rssl|safari|extz|svgz?
|swf|topo.json|tt[cf]|txt|vcard|vcf|vtt|webapp|web[mp]|woff2?|x|ocl|xml|xpi)$">
# Header unset X-XSS-Protection
# </FilesMatch>
```

```

# </IfModule>
# -----
# | Server software information |
# -----
# Prevent Apache from sending in the `Server` response header its
# exact version number, the description of the generic OS-type or
# information about its compiled-in modules.
#
# (!) The `ServerTokens` directive will only work in the main server
# configuration file, so don't try to enable it in the `.htaccess` file!
#
# https://httpd.apache.org/docs/current/mod/core.html#servertokens
# ServerTokens Prod
# #####
# # WEB PERFORMANCE #
# #####
# -----
# | Compression |
# -----
<IfModule mod_deflate.c>
# Force compression for mangled `Accept-Encoding` request headers
# https://developer.yahoo.com/blogs/ydn/pushing-beyond-gzipping-25601.html
<IfModule mod_setenvif.c>
<IfModule mod_headers.c>
SetEnvIfNoCase ^(\Accept-EncodXng|X-cept-Encoding|X(15)|^(15)|-(15))$ ^((gzip|deflate)\s*,?
\s*)+|[X^-]{4,13}$ HAVE_Accept-Encoding
RequestHeader append Accept-Encoding "gzip, deflate" env=HAVE_Accept-Encoding
</IfModule>
</IfModule>
# -----
# Compress all output labeled with one of the following media types.
#
# (!) For Apache versions below version 2.3.7 you don't need to
# enable `mod_filter` and can remove the `<IfModule mod_filter.c>`
# and `</IfModule>` lines as `AddOutputFilterByType` is still in
# the core directives.
#
# https://httpd.apache.org/docs/current/mod/mod_filter.html#addoutputfilterbytype
<IfModule mod_filter.c>
AddOutputFilterByType DEFLATE "application/atom+xml" \
"application/javascript" \

```

```
"application/json" \
"application/ld+json" \
"application/manifest+json" \
"application/rdf+xml" \
"application/rss+xml" \
"application/schema+json" \
"application/vnd.geo+json" \
"application/vnd.ms-fontobject" \
"application/x-font-ttf" \
"application/x-javascript" \
"application/x-web-app-manifest+json" \
"application/xhtml+xml" \
"application/xml" \
"font/eot" \
"font/opentype" \
"image/bmp" \
"image/svg+xml" \
"image/vnd.microsoft.icon" \
"image/x-icon" \
"text/cache-manifest" \
"text/css" \
"text/html" \
"text/javascript" \
"text/plain" \
"text/vcard" \
"text/vnd.rim.location.xloc" \
"text/vtt" \
"text/x-component" \
"text/x-cross-domain-policy" \
"text/xml"
```

```
</IfModule>
```

```
# -----
```

```
# Map the following filename extensions to the specified  
# encoding type in order to make Apache serve the file types  
# with the appropriate `Content-Encoding` response header  
# (do note that this will NOT make Apache compress them!).  
#  
# If these files types would be served without an appropriate  
# `Content-Enable` response header, client applications (e.g.:  
# browsers) wouldn't know that they first need to uncompress  
# the response, and thus, wouldn't be able to understand the
```



```
# content,
#
# https://httpd.apache.org/docs/current/mod/mod\_mime.html#addencoding
<IfModule mod_mime.c>
AddEncoding gzip svgz
</IfModule>
</IfModule>
# -----
# | Content transformation |
# -----
# Prevent intermediate caches or proxies (e.g.: such as the ones
# used by mobile network providers) from modifying the website's
# content,
#
# https://tools.ietf.org/html/rfc2616#section-14.9.5
#
# (!) If you are using `mod_pagespeed`, please note that setting
# the `Cache-Control: no-transform` response header will prevent
# `PageSpeed` from rewriting `HTML` files, and, if the
# `ModPagespeedDisableRewriteOnNoTransform` directive isn't set
# to `off`, also from rewriting other resources,
#
# https://developers.google.com/speed/pagespeed/module/configuration#notransform
# <IfModule mod_headers.c>
# Header merge Cache-Control "no-transform"
# </IfModule>
# -----
# | ETags |
# -----
# Remove `ETags` as resources are sent with far-future expires headers,
#
# https://developer.yahoo.com/performance/rules.html#etags
# https://tools.ietf.org/html/rfc7232#section-2.3
# `FileETag None` doesn't work in all cases,
<IfModule mod_headers.c>
Header unset ETag
</IfModule>
FileETag None
# -----
# | Expires headers |
# -----
```

```
..
# Serve resources with far-future expires headers.
#
# (!) If you don't control versioning with filename-based
# cache busting, you should consider lowering the cache times
# to something like one week.
#
# https://httpd.apache.org/docs/current/mod/mod_expires.html
<IfModule mod_expires.c>
ExpiresActive on
ExpiresDefault "access plus 1 month"
# CSS
ExpiresByType text/css "access plus 1 year"
# Data interchange
ExpiresByType application/atom+xml "access plus 1 hour"
ExpiresByType application/rdf+xml "access plus 1 hour"
ExpiresByType application/rss+xml "access plus 1 hour"
ExpiresByType application/json "access plus 0 seconds"
ExpiresByType application/ld+json "access plus 0 seconds"
ExpiresByType application/schema+json "access plus 0 seconds"
ExpiresByType application/vnd.geo+json "access plus 0 seconds"
ExpiresByType application/xml "access plus 0 seconds"
ExpiresByType text/xml "access plus 0 seconds"
# Favicon (cannot be renamed!) and cursor images
ExpiresByType image/vnd.microsoft.icon "access plus 1 week"
ExpiresByType image/x-icon "access plus 1 week"
# HTML
ExpiresByType text/html "access plus 0 seconds"
# JavaScript
ExpiresByType application/javascript "access plus 1 year"
ExpiresByType application/x-javascript "access plus 1 year"
ExpiresByType text/javascript "access plus 1 year"
# Manifest files
ExpiresByType application/manifest+json "access plus 1 year"
ExpiresByType application/x-web-app-manifest+json "access plus 0 seconds"
ExpiresByType text/cache-manifest "access plus 0 seconds"
# Media files
ExpiresByType audio/ogg "access plus 1 month"
ExpiresByType image/bmp "access plus 1 month"
ExpiresByType image/gif "access plus 1 month"
ExpiresByType image/jpeg "access plus 1 month"
ExpiresByType image/png "access plus 1 month"
```

```

ExpiresByType image/png "access plus 1 month"
ExpiresByType image/svg+xml "access plus 1 month"
ExpiresByType video/mp4 "access plus 1 month"
ExpiresByType video/ogg "access plus 1 month"
ExpiresByType video/webm "access plus 1 month"
# Web fonts
# Embedded OpenType (EOT)
ExpiresByType application/vnd.ms-fontobject "access plus 1 month"
ExpiresByType font/eot "access plus 1 month"
# OpenType
ExpiresByType font/opentype "access plus 1 month"
# TrueType
ExpiresByType application/x-font-ttf "access plus 1 month"
# Web Open Font Format (WOFF) 1.0
ExpiresByType application/font-woff "access plus 1 month"
ExpiresByType application/x-font-woff "access plus 1 month"
ExpiresByType font/woff "access plus 1 month"
# Web Open Font Format (WOFF) 2.0
ExpiresByType application/font-woff2 "access plus 1 month"
# Other
ExpiresByType text/x-cross-domain-policy "access plus 1 week"
</IfModule>
# -----
# | File concatenation |
# -----
# Allow concatenation from within specific files.
#
# e. g.:
#
# If you have the following lines in a file called, for
# example, `main.combined.js`:
#
# <!--#include file="js/jquery.js" -->
# <!--#include file="js/jquery.timer.js" -->
#
# Apache will replace those lines with the content of the
# specified files.
# <IfModule mod_include.c>
# <FilesMatch "\.combined\.js$" >
# Options +Includes
# AddOutputFilterByType INCLUDES application/javascript \
# -----

```

```

# application/javascript \
# text/javascript
# SetOutputFilter INCLUDES
# </FilesMatch>
# <FilesMatch "\.combined\.css$" >
# Options +Includes
# AddOutputFilterByType INCLUDES text/css
# SetOutputFilter INCLUDES
# </FilesMatch>
# </IfModule>
# -----
# | Filename-based cache busting |
# -----
# If you're not using a build process to manage your filename version
# revving, you might want to consider enabling the following directives
# to route all requests such as `/style.12345.css` to `/style.css`.
#
# To understand why this is important and even a better solution than
# using something like `*.css?v231`, please see:
# http://www.stevesouders.com/blog/2008/08/23/revving-filenames-dont-use-querystring/
# <IfModule mod_rewrite.c>
# RewriteEngine On
# RewriteCond %{REQUEST_FILENAME} !-f
# RewriteRule ^(.+)\.(\d+)\. (bmp|css|curl|gif|ico|jpe?g|js|png|svgz?|webp)$ $1.$3 [L]
# </IfModule>

# prevent httpd from serving dotfiles (.htaccess, .svn, .git, etc.)
RedirectMatch 403 /\..*$
# if a directory or a file exists, use it directly
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
# otherwise forward it to index.php
RewriteRule . index.php

```